





MIURA PLUS

AUTOMATIC XY CUTTER WITH AUTOMATIC VERTICAL ALIGNMENT

High performing cutting machine for X and Y trimming of flexible materials with automatic vertical cutting correction.

HIGH PRODUCTIVITY

Combined horizontal and vertical cutting for the fastest finish for your printed and unprinted rolls

MAXIMUM CUTTING PRECISION

The **edge control** guarantees a perfect straight cutting of the media roll

HIGH PERFORMING

It cuts one roll of 50 meters (164 ft) in less than 5 minutes

LOW MAITENANCE COSTS

Miura ensures low costs maintenance. Blade replacement is simple and needs just a few minutes

✓ LONG-TERM RELIABILITY AND SAFETY

The lengthwise rotary crush cutters last for 100's of thousands of cuts and are safe for the operator

TOUCH SCREEN DISPLAY

Intuitive set up of the cut parameters

CUTTING FLEXIBILITY

3 cutting modes: 1. automatic by crop marks; 2. sheeting; 3. manual: Miura can trim different lenghts from the same printed roll

SMART REMOTE SYSTEM

Miura can be connected to the internet network for remote assistance, for fast and efficient diagnostics

SUITABLE MATERIALS:

- > Paper (also laminated or encapsulated) / Wallpaper
- > Vinyl & self adhesive vinyl / Backlit & frontlit display
- > Canvas & poliestere (with liner)
- > PVC banner (up to 900 gr/m² 27 oz./ya²)
- > Magnetic rubber / Polycarbonate (film)
- > Reflective material / Many more...





Automatic vertical alignment control panel



Optical sensor for vertical alignment



Advanced cutting mark reader



User-friendly software design



Fine positioning of the cutting blades (optional)



Single lengthwise rotary crush cutter (twin cutters optional)



Can be fitted with: (optional): 1. Motorized Stacker in line with

the cutter: height and inclination electronically adjustable; extensible length up to 3,2 meters

2. Folding collecting table

3. NEW Tiltable collecting table with wheels



Fine pressure adjustment (according to the types of material)



Slimline lengthwise rotary crush cutter, single or twin, (optional)



Clean working area thanks to the big waste basket

	MIURA 160 PLUS	MIURA 210 PLUS	MIURA 265 PLUS
Working width	1650 mm (65 in)	2150 mm (84 in)	2650 mm (104 in)
Maximum cutting thickness	1,2 mm (0,04 in)	1,2 mm (0,04 in)	1,2 mm (0,04 in)
Feeding speed	1 - 30 m/min. (3 - 98 ft/min)	1 - 30 m/min. (3 - 98 ft/min)	1 - 30 m/min. (3 - 98 ft/min)
Usable cutting units	max. 8	max. 8	max. 8
Cross cutting speed	5-120 m/min (16-393 ft/min)	5-120 m/min (16-393 ft/min)	5-120 m/min (16-393 ft/min)
Max. roll diameter	300 mm (12 in)	300 mm (12 in)	300 mm (12 in)
Max. roll weight	60 kg (132 lbs)	60 kg (132 lbs)	60 kg (132 lbs)
Power supply	230 V - 50 Hz - 650 W	230 V - 50 Hz - 650 W	230 V - 50 Hz - 650 W
Dimensions (W x D x H)	2460 x 1000 x 1330 mm (96 x 39 x 52 in)	2960 x 1000 x 1330 mm (116 x 39 x 52 in)	3460 x 1000 x 1330 mm (136 x 39 x 52 in)
Weight	415 kg (881 lbs)	460 kg (1014 lbs)	530 kg (1168 lbs)
Packing dimensions (W x D x H)	2650 x 1150 x 1650 mm (104 x 45 x 65 in)	3250 x 1250 x 1700 mm (128 x 49 x 67 in)	3750 x 1250 x 1700 mm (147 x 49 x 67 in)
Packing weight	500 kg (1102 lbs)	630 kg (1388 lbs)	728 kg (1604 lbs)

Manufactured in compliance with CE regulations



Follow us:

















100% Made in Italy

